

Bevi 2.0 Pre-Installation Checklist

Thank you for being a Quench customer! We are excited for your workplace to experience the great-tasting sparkling and flavored water from your new Bevi 2.0. Before our certified technician can install your machine, the following pre-installation requirements must be completed.

Water Supply

- 1/4" potable water supply line
- Minimum water supply pressure 40 PSI, 1.3 gallon per minute minimum flowrate
 - Must be a dedicated 1/4" water supply line with no other connections
 - Any water line or valve less than 1/4" is not acceptable
- Note: Bevi 2.0 is equipped with an ASSE 1032-certified back flow preventer device

Electrical

- Dedicated 115 VAC/60Hz/15 amp or 20 amp (standard 3-prong) GFCI-protected circuit
 - Machine draws 12 amps
- Electrical connections within 10' of machine location; **NO EXTENSION CORDS**

Placement

- Need to be installed on a sturdy, level surface suitable for holding 250 lbs.
- Requires at least 2' of clearance at the front of the machine to allow the door to be opened for servicing
- Bevi 2.0 has a footprint of 16.5" w x 21.25" d plus appropriate ventilation

Ventilation

- Requires 1" clearance on either side with 2" in the back for ventilation
- At least 3" clearance is required on the top of the machine for ventilation
- Bevi 2.0 total footprint, including ventilation is 18.5" w x 23.25" d x 69.5" h

CO₂ Supply

- CO₂ cylinder is on-site
 - Quench service technician will typically deliver CO₂ for installation; confirm with your sales representative
 - A 20 lb. tank of CO₂ fits snugly inside the base of the Bevi 2.0
- For optimum performance, Quench recommends using CO₂ cylinders instead of connecting to a bulk or CO₂ system
 - Minimum CO₂ pressure is 80 PSI

If you have any questions about the installation, call Customer Care at 888-554-2782

